



## The Power of IP to Enhance Business Communications

Take enterprise-wide communication to a whole new level—with an IP communication system that integrates your voice, data networking, and applications solutions. One that combines the advantages of network-based telephony and the features of traditional PBX systems, as well as valuable options like Voice Mail/Auto Attendant/Unified Messaging, Automatic Call Distribution, StrataNet multiple system networking, FeatureFlex™ adaptability/customization tools, and more to improve your business' overall productivity and customer service.

Strata CIX™ systems are designed to work exactly as you need today, in one or multiple locations, while enabling you to grow and add other capabilities in the future. The Strata CIX is the ultimate, modular, scalable, networkable telephone system for your business.

### SPECIFICATIONS

Model	Strata CIX200			
Capacities	96 CO lines/160 station users (192 Universal ports).			
Chassis Measurements Base Cabinet	Width	Height	Depth	Weight
Metric	440 mm without bracket 483 mm with bracket	89 mm	410 mm	7.2 kg
English	17.3 in. without bracket 19 in. with bracket	3.5 in.	16.1 in.	16 lbs.
Chassis Measurements Expansion Cabinet	Width	Height	Depth	Weight
Metric	440 mm without bracket (483 mm with bracket)	89 mm	410 mm	7.2 kg
English	17.3 in. without bracket 19 in. with bracket	3.5 in.	16.1 in.	16 lbs.
Power Supply Unit (PSU)	Initially Built-in (one per cabinet)			
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (45Hz - 65Hz). 480 watts per cabinet (maximum).			
Power Backup	An Uninterruptible Power Supply (UPS) is required for power backup on a CIX200. The UPS is similar to the ones used for computer systems and networking equipment.			
Chassis Installation	19" Rack-mount (preferred) or Table top. Standard 19" rack-mounting, IEC297-1 (EIA RS 310-D), 465.1mm (front face screw pitch-width).			
Compliance	Safety: UL EMC: FCC Part 15 Class A (Subpart A) HAC and Volume Control: FCC Part 68 Network safety: TIA-968-2-A			

FCC Registration	PBX: CJ6PF03BDTCHS192 Hybrid: CJ6MF03BDTCHS192 Key: CJ6KD03BDTCHS192
Operating Temperature	32~104° F (0~40° C)
Operating Humidity	20~80% relative humidity without condensation
Storage Temperature	-4~140° F (-20~60° C)
Voice Mail Compatibility	Strata Media Application Server, Stratagy® ES, iES32, iES16, IVP8
CO Line Compatibility	Analog: Loop or ground start, DID, E&M Digital: T1, ISDN PRI and BRI IP: Strata Net IP E911: CAMA and ISDN PRI
IP Telephone Compatibility	Toshiba Charcoal Gray MEGACO+ models: <ul style="list-style-type: none"> <li>• IPT2010-SD full-duplex speakerphone with 10 programmable buttons and 2-line x 24-character LCD.</li> <li>• IPT2010-SDC full-duplex speakerphone with 10 programmable buttons and 2-line x 24-character LCD and analog CO line interface.</li> <li>• IPT2020-SD full-duplex speakerphone with 20 programmable buttons and 2-line x 24-character LCD.</li> <li>• IPT2008-SDL full-duplex speaker phone with 8 programmable buttons and large 144 x 128 pixel display with HTML support.</li> </ul> 802.3af Power-over-Ethernet compliant. Ethernet switch for PC connection to your IP Network. 802.1Q Virtual Local Area Network (VLAN) compliant. Hitachi WIP5000E-A Wireless SIP Telephone. Uniden UIP 200 SIP Telephone.
Digital Telephone Compatibility	Toshiba 3200-Series Charcoal Gray models: <ul style="list-style-type: none"> <li>• DKT3201 single-line telephone.</li> <li>• DKT3210-S speakerphone with 10 programmable buttons.</li> <li>• DKT3220-S speakerphone with 20 programmable buttons.</li> <li>• DKT3210-SD speakerphone with 10 programmable buttons and 2-line x 24-character LCD.</li> <li>• DKT3220-SD speakerphone with 20 programmable buttons and 2-line x 24-character LCD.</li> <li>• DKT3214-SDL speakerphone with 14 programmable buttons and large 8-line x 24-character LCD.</li> </ul> Toshiba 3000-Series Ash White models: <ul style="list-style-type: none"> <li>• DKT3001 (W) single-line telephone.</li> <li>• DKT3010-S (W) speakerphone with 10 programmable buttons.</li> <li>• DKT3020-S (W) speakerphone with 20 programmable buttons.</li> <li>• DKT3010-SD (W) speakerphone with 10 programmable buttons and 2-line x 24-character LCD.</li> <li>• DKT3020-SD (W) speakerphone with 20 programmable buttons and 2-line x 24-character LCD.</li> <li>• DKT3014-SDL (W) speakerphone with 14 programmable buttons and large 8-line x 24-character LCD.</li> </ul>
Analog Device Compatibility	Dealer-supplied standard telephones with or without Caller ID, FAX machines, modems, etc.
Answer Position Options	20-button Add-On Module (Available in Ash White & Charcoal Gray) 60-button DSS/BLF Console (Available in Ash White & Charcoal Gray) Strata PC Attendant Console
User Mobility Options	SoftIPT™ soft phone client on laptop or tablet PC via wi-fi W-LAN. SoftIPT soft phone client on PDA via wi-fi W-LAN. Wireless IP telephone support via wi-fi W-LAN. Cordless digital telephone.
System Administration	Browser-based unified administration of PBX and voice mail functions. eManager™ installation/maintenance for technicians and administrators. eMonitor monitoring of alarm conditions from multiple Strata CIX systems. My Phone Manager™ personal administration for individual users. Traffic measurement reports stored on local SD flash memory card.
Standard System Features	Over 300 standard telephony features to provide the functionality you need.
Advanced Application Options	Add valuable options like Voice Mail/Auto Attendant, Unified Messaging, Automated Speech Recognition, Text-to-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, StrataNet multiple system networking, Info Manager™ Web-based telephone applications, FeatureFlex adaptability/customization tools, uniform call distribution, centralized network SMDR, and more.
Multi-system Networking	StrataNet networking of up to 128 nodes via IP or ISDN PRI.
Feature Customization	FeatureFlex adaptability tools for feature creation/customization.

## Toshiba America Information Systems, Inc., Telecommunication Systems Division

9740 Irvine Blvd., Irvine, CA 92618-1697 (949) 583-3700 [www.telecom.toshiba.com](http://www.telecom.toshiba.com)

© 2007 Toshiba America Information Systems, Inc., Telecommunication Systems Division. Printed in U.S.A. Strata is a registered trademark of Toshiba Corporation. Stratagy is a registered trademark of Toshiba America Information Systems, Inc. Specifications subject to change without notice. Some features require optional hardware/software to support full capabilities.

Literature Order #: TSD-CIX-BR-200-DS-VD/4500092